# **Bobcat S130 Skidloader**

## S130 Key Specifications

Horsepower	46 hp
Rated Operating Capacity (ISO)	1,300 lb
Operating Weight	5063 lb
Auxiliary Std Flow	16.9 gal/min
Joystick control	Not Applicable

### **Engine**

Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	46
Turbocharged Engine	No
emissions Tier (EPA)	N/A

#### **Performance**

Rated Operating Capacity (ISO)	1,300 lb
Tipping Load	2744 lb
Operating Weight	5036 lb
Travel Speed	7.3 mph

## Capacities

Fuel Tank	13.3 gal

## Hydraulic System

System Relief @ Quick Couplers	3,135 psi
Auxiliary Std Flow	16.9 gal/min

#### **Dimension**

Length	124.1 in
Length without Attachment	95.8 in
Length with Standard Bucket	124.1 in
Width	58.7 in
Width (with bucket)	62 in
Height	77.3 in
Height with Operator Cab	77.3 in
Height to Bucket Hinge Pin	109.5 in
Reach @ Maximum Height	22.6 in
Turning Radius	68.7 in
Wheelbase	35.5

#### Features

Joystick Control	Not Applicable
Air Conditioning	Not Applicable
Adjustable Seat	Standard
BICS System (Interlock)	Standard
Cab Enclosure	Optional
Sound Option	Optional
Cab Heater	Optional
Rear Window	Standard
Lift-Arm Support	Standard
Suspension Seat	Optional
Two Speed Travel	Not Applicable
Deluxe Instrumentation	Optional
Engine Shutdown	Standard
Hydraulic Bucket Positioning	Optional
High Flow Option	Not Applicable
Auxiliary Hydraulics	Standard
Bob-Tach Attachment System	Standard
Power Bob-Tach	Optional
Ride Control	Not Applicable