



# 3522 A - 3632 T - 4527 A - 5533 A - 6543 A



## TRAILER-MOUNTED BOOMS

	3522 A	3632 T	4527 A	5533 A	6543 A
Working height	41 ft 9 in	43 ft 6 in	51 ft	61 ft 3 in	71 ft
Platform height	35 ft 9 in	37 ft 6 in	45 ft	55 ft 3 in	65 ft
Horizontal outreach (from centerline)	22 ft 6 in	32 ft	27 ft	33 ft 5 in	43 ft
Horizontal outreach (from edge of footpad)	17 ft 5 in	27 ft	21 ft	27 ft 4 in	37 ft
Up and over height	19 ft	N/A	20 ft 9 in	23 ft 1 in	24 ft 2 in
Lift capacity			500 lbs		
A - Length - stowed	16 ft 3 in	22 ft 8 in	20 ft 8 in	23 ft 8 in	24 ft
B - Width stowed		5 ft 6 in		5 ft 7 in	5 ft 11 in
C - Height stowed		6 ft 8 in		6 ft 9 in	7 ft
D x E - Platform size			4 ft 1 in x 2 ft 9 in		
F - Widest Point	11 ft 10 in	13 ft 9 in	13 ft 9 in	14 ft 8 in	14 ft 8 in
G - Widest Point	12 ft 2 in	13 ft 6 in	13 ft 6 in	15 ft	15 ft
Turntable rotation			350° non-continuous		
Jib - length	4 ft 3 in	N/A		4 ft 3 in	
Jib - Vertical Motion	150° (+70 / -80)	N/A		150° (+70 / -80)	
Tow speed rating			65 mph		
Leveling capability			12.5 °		
Tire size	ST 225/75 D15		ST 225/75 R15		ST 215/75R 17.5
Power source			4 x 6 V 245 amp-hr		
Tongue weight (no options)	245 lbs	200 lbs	290 lbs	335 lbs	550 lbs
Weight (no options)	3400 lbs	4440 lbs	4200 lbs	4800 lbs	7700 lbs

- Hydraulic outriggers
  - Tilt alarm/sensor
  - Hour meter and battery condition indicator
  - Automatic leveling system and self-leveling platform
  - 110V GFI protected outlet to platform
  - Easy to use controls
  - Air and water line to platform
  - Inboard 25 amp charger
  - Integrated forklift pockets
  - Hydraulic surge brakes (trailer)
- 
- Spare tire and mounting kit
  - DC / Gas hybrid
  - Manual platform rotator - 120° stop point to stop point
  - Flashing beacon
  - Fluorescent tube caddy
  - Combination hitch
  - Tool tray
  - Electric brakes (trailer)
  - Drive and Set

